


NASA/CR-2000-210631
ICASE Report No. 2000-48



Mapping Closure Approximation to Conditional Dissipation Rate for Turbulent Scalar Mixing

*Guowei He and R. Rubinstein
ICASE, Hampton, Virginia*



December 2000

The NASA STI Program Office . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers, but having less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.

- **CONFERENCE PUBLICATIONS.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized data bases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at <http://www.sti.nasa.gov>
- Email your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA STI Help Desk at (301) 621-0134
- Telephone the NASA STI Help Desk at (301) 621-0390
- Write to:
NASA STI Help Desk
NASA Center for AeroSpace Information
7121 Standard Drive
Hanover, MD 21076-1320

NASA/CR-2000-210631
ICASE Report No. 2000-48



Mapping Closure Approximation to Conditional Dissipation Rate for Turbulent Scalar Mixing

*Guowei He and R. Rubinstein
ICASE, Hampton, Virginia*

*ICASE
NASA Langley Research Center
Hampton, Virginia*

Operated by Universities Space Research Association



National Aeronautics and
Space Administration

Langley Research Center
Hampton, Virginia 23681-2199

Prepared for Langley Research Center
under Contract NAS1-97046

December 2000

Available from the following:

NASA Center for AeroSpace Information (CASI)
7121 Standard Drive
Hanover, MD 21076-1320
(301) 621-0390

National Technical Information Service (NTIS)
5285 Port Royal Road
Springfield, VA 22161-2171
(703) 487-4650

MAPPING CLOSURE APPROXIMATION TO CONDITIONAL DISSIPATION RATE FOR TURBULENT SCALAR MIXING

GUOWEI HE* AND R. RUBINSTEIN†

Abstract. A novel mapping closure approximation (MCA) technique is developed to construct a model for the conditional dissipation rate (CDR) of a scalar in homogeneous turbulence. It is shown that the CDR model from amplitude mapping closure is incorrect in asymptotic behavior for unsymmetric binary mixing. The correct asymptotic behavior can be described by the CDR model formulated by the MCA technique. The MCA approach is outlined for constructing successive approximation to probability density function (PDF) and conditional moment.

Key words. turbulent mixing, mapping closure, conditional dissipation rate, probability density function

Subject classification. Fluid Mechanics

1. Introduction. The probability density function (PDF) approach has been shown to be a useful tool in turbulence research. The systematic approach for determining the PDFs is by means of solving the transport equations for the PDFs. In the PDF equations for turbulent scalar fields, conditional dissipation rate (CDR) appears as the only unclosed term [1]. The recently developed large-eddy simulation schemes for turbulent reactive flow, such as filtered PDF approach [2], conditional moment closure [3] and Lagrangian flamelet model [4] also appeal the CDR models.

No satisfactory closure model for CDR had been constructed until the mapping closure approach [5, 6] was formulated. Amplitude mapping closure suggests a CDR model [7] whose form is separable in scalar and time variables. The model is in good agreement with direct numerical simulation (DNS) for initially symmetric binary mixing but fails in describing asymptotic behavior of the CDR for initially unsymmetric binary mixing [8]. Girimaji [9] has developed a novel amplitude mapping closure approach in which the reference fields are time-dependent. The CDR model obtained from a time-evolving Gaussian reference field still fails to describe the asymptotic behavior, but the one from a time-evolving Beta reference field can successfully describe the asymptotic behavior. This strongly suggests that the amplitude mapping closure is inadequate to describe the asymptotic behavior by itself.

In this paper, we will develop a novel mapping closure approximation (MCA) to make successive approximations to statistics of a scalar in homogeneous turbulence. This technique will be used to construct a CDR model which accounts for the asymptotic behavior of the CDR. In Section 2, we will investigate the asymptotic behavior of the CDR model from amplitude mapping closure and explain the reason why it fails to describe the asymptotic behavior correctly. In section 3, we will outline the MCA technique for successive approximation. In section 4, we will use the MCA technique to formulate a novel CDR model and compare it with DNS results. We will conclude with a summary in section 5.

*ICASE, Mail Stop 132C, NASA Langley Research Center, Hampton, VA 23681-0001 (email:hgw@icase.edu). This research was supported by the National Aeronautics and Space Administration under NASA Contract No. NAS1-97046 while the author was in residence at ICASE, NASA Langley Research Center, Hampton, VA 23681.

†ICASE, Mail Stop 132C, NASA Langley Research Center, Hampton, VA 23681-0001 (email:bobr@icase.edu). This research was supported by the National Aeronautics and Space Administration under NASA Contract No. NAS1-97046 while the author was in residence at ICASE, NASA Langley Research Center, Hampton, VA 23681.

2. Asymptotic behaviors of amplitude mapping closure. In this section, we will show that the CDR model from amplitude mapping closure has incorrect asymptotic behavior for unsymmetric binary mixing. We consider the simple case of a single conserved scalar $Z(x, t)$ in incompressible homogeneous and isotropic turbulence. With $u(x, t)$ being the velocity field and κ the molecular diffusivity, the evolution equation for scalar Z is

$$(2.1) \quad \frac{\partial Z}{\partial t} + \mathbf{u} \cdot \nabla Z = \kappa \nabla^2 Z.$$

Here the boundary condition is periodic and the scalar is initially homogeneous and isotropic. Therefore, the scalar $Z(x, t)$ will remain homogeneous and isotropic for all time. We further assume that the scalar is binary (0 or 1) and its initial PDF is a double-delta distribution:

$$(2.2) \quad P(Z, 0) = \begin{cases} A & \text{if } Z = 0 \\ 1 - A & \text{if } Z = 1 \\ 0 & \text{if } Z \neq 0 \text{ or } 1, \end{cases}$$

where $0 \leq A \leq 1$. $A = 0.5$ implies that the binary scalar has the same weights and the corresponding PDF $P(Z, 0)$ is symmetric with respect to $Z = 0.5$, while $A \neq 0.5$ implies that the binary scalar has different weights and the corresponding PDF $P(Z, 0)$ is unsymmetric. DNS [10] has shown that the scalar PDF $P(Z, t)$ asymptotically approaches a Gaussian distribution, whether the initial double-delta distribution is symmetric or unsymmetric. The mean $\langle Z \rangle = 1 - A$ remains unchanged in turbulent mixing. The CDR $\chi(Z, t) = \kappa \langle (\nabla Z)^2 | Z \rangle$ is nearly parabolic. At early stages, the CDR maximum is located at $Z = 0.5$, the mean of the initial interface of the binary scalar. The maximum then moves and finally approaches the mean $\langle Z \rangle$ of the scalar, accompanied by a distortion of the parabola. Therefore, for an initially symmetric binary scalar ($A = 0.5$), the maximum will remain fixed at $Z = 0.5$, where the mean of the scalar and the mean of the initial interface are coincident. For an initially unsymmetric binary scalar ($A \neq 0.5$), the maximum will shift to the mean $Z = 1 - A$ of the scalar from the mean $Z = 0.5$ of the initial interface.

Amplitude mapping closure assumes

$$(2.3) \quad Z = X(\phi_0, t),$$

where $\phi_0(\mathbf{x})$ is a homogeneous Gaussian random field. The governing equation for the mapping function X is

$$(2.4) \quad \frac{\partial X}{\partial t} = \kappa \langle \phi_{0,x}^2 \rangle \left(-\frac{\phi_0}{\langle \phi_0^2 \rangle} \frac{\partial X}{\partial \phi_0} + \frac{\partial^2 X}{\partial \phi_0^2} \right),$$

where $\phi_{0,x}$ is the spatial gradient of the scalar ϕ_0 . The initial mapping function corresponding to (2.2) is

$$(2.5) \quad X(\phi_0, 0) = \begin{cases} 0 & \text{if } \phi_0 \leq \gamma \\ 1 & \text{if } \phi_0 > \gamma, \end{cases}$$

where $\gamma = \sqrt{2} \operatorname{erf}^{-1}(2A - 1)$. The exact solution of the equation (2.4) with the initial condition (2.5) is

$$(2.6) \quad X(\phi_0, t) = \frac{1}{2} \left[1 + \operatorname{erf} \left(\frac{\theta_0 - \gamma e^\tau}{\sqrt{2\Sigma}} \right) \right],$$

where

$$(2.7) \quad \begin{aligned} \theta_0 &= \frac{\phi_0}{\sqrt{\langle \phi_0^2 \rangle}}, \\ \tau &= \kappa \frac{\langle \phi_{0x}^2 \rangle}{\langle \phi_0^2 \rangle} t, \\ \Sigma &= \sqrt{\exp(2\tau) - 1}. \end{aligned}$$

We can calculate the CDR from the exact solution (2.6)

$$(2.8) \quad \begin{aligned} \chi(Z, t) &= \kappa \frac{\langle \phi_{0x}^2 \rangle}{\langle \phi_0^2 \rangle} \frac{1}{\sqrt{2\pi\Sigma}} \exp \left(-2 \left[\operatorname{erf}^{-1}(2Z - 1) \right]^2 \right) \\ &= \chi(0.5, t) \exp \left(-2 \left[\operatorname{erf}^{-1}(2Z - 1) \right]^2 \right). \end{aligned}$$

The most striking feature of the CDR model (2.8) is the separability of its form in Z and t . The separability suggests that the CDR's shape remains unchanged although its amplitude decays with time. The CDR maximum is located permanently at $Z = 0.5$ without any shift for either symmetric or unsymmetric initial conditions. The permanent location of the maximum for unsymmetric initial condition [7, 8, 9] is contrary to the known asymptotic behavior of the CDR. Therefore, the CDR model (2.8) from amplitude mapping closure is not able to describe the asymptotic behavior of the CDR. The amplitude mapping closure with a time-evolving Gaussian reference field gives a similar CDR model whose form is separable in t and Z and also fails to describe the shift of the maximum. Therefore, the separation in form is the main reason for the incorrect asymptotic behavior of the CDR model from amplitude mapping closure.

3. Mapping closure approximation. The basic idea of mapping closure is to represent an unknown random field by mapping of a known random reference field. The statistics of the unknown random field can be calculated from the mapping function and the known reference field. The governing equation for the mapping function can be obtained from the evolution equation of the unknown random field and the governing equation of its PDF.

Amplitude mapping closure assumes that the unknown random field can be mapped by a single known Gaussian reference field: $Z = X(\phi(x'), t)$ and a coordinate transformation $dx'/dx = J(d\phi(x')/dx', t)$ that accounts for turbulent stretching. The assumption [11] holds if and only if the spatial level crossing frequency at which the unknown random field passes through a given value has a single maximum as a function of that value. Therefore, the existence of the mapping function as well as the coordinate transformation is not ensured for arbitrary unknown random fields. Physically, a turbulent field exhibits eddies of different length and time scales so that it cannot be mapped by a single reference Gaussian field with a compact spectrum. Therefore, it is necessary to introduce more reference fields accounting for different eddies of different time and length scales:

$$(3.1) \quad Z = X(\phi_0(x, t), \phi_1(x, t), \dots, \phi_n(x, t); x, t)$$

where ϕ_i , $i = 1, \dots, n$, are reference fields. So far, we have not imposed any constraints on the reference fields so that we have some freedom in choosing the reference fields. For example, ϕ_0 could be Gaussian but ϕ_1 could be a Beta random field.

A one-to-one mapping could be established artificially between $(Z, \phi_1, \dots, \phi_n)$ and $(\phi_0, \phi_1, \dots, \phi_n)$. Thus, we can calculate the PDF and the conditional dissipation rate of the scalar

$$(3.2) \quad P(Z; x, t) = \int P(\phi_0, \phi_1, \dots, \phi_n) \left(\frac{\partial X}{\partial \phi_0} \right)^{-1} d\phi_1 \dots d\phi_n,$$

$$(3.3) \quad \langle (\nabla Z)^2 | Z \rangle = \langle (\nabla X)^2 | Z \rangle.$$

Here the integration is taken over the entire subspace of the composition ϕ_1, \dots, ϕ_n . The ensemble average is taken over the level surface on which $(\phi_0, \phi_1, \dots, \phi_n)$ satisfies the constraint for a given Z

$$(3.4) \quad X(\phi_0(x, t), \phi_1(x, t), \dots, \phi_n(x, t); x, t) = Z.$$

Introduction of more reference fields is expected to improve the approximation accuracy of mapping closure. The reference fields might be chosen to be statistically orthogonal so that more information can be introduced at less expenses. The hierarchy of mapping closure approximations with an increasing number of reference fields remains essentially non-perturbative. A perturbative approach, like the Wiener-Hermite expansion [13], could lead to the same result, but would require a prohibitively large number of terms to achieve the accuracy attainable with mapping closure based on a small number of reference fields.

4. The model for conditional dissipation rate. Broad classes of mapping function are admissible to MCA approach. The form to be considered here is

$$(4.1) \quad Z = Y(\phi_0(x), \phi_1(t); t),$$

where $\phi_0(x)$ is a homogeneous random Gaussian field in space and $\phi_1(t)$ an inhomogeneous random Gaussian field in time. Amplitude mapping closure requires $\phi_1(t) = 0$, which fails in the asymptotic behavior of conditional dissipation rate due to lack of an independent time-evolving reference field.

Following the standard method [11, 12], we can formulate the mapping equation:

$$(4.2) \quad \frac{\partial Y}{\partial t} + \frac{\partial Y}{\partial \phi_1} \left\langle \frac{d\phi_1}{dt} \middle| Z \right\rangle = -\langle u \nabla Y | Z \rangle + \kappa \langle \nabla^2 Y | Z \rangle.$$

The conditional averages in (4.2) can be evaluated by homogeneity of the velocity and scalar fields and Gaussianity of the reference fields

$$(4.3) \quad \begin{aligned} \langle u \nabla Y | Z \rangle &= 0, \\ \left\langle \frac{d\phi_1}{dt} \middle| Z \right\rangle &= \frac{\phi_1}{2\langle \phi_1^2 \rangle} \frac{d\langle \phi_1^2 \rangle}{dt}, \\ \langle \nabla^2 Y | Z \rangle &= -\phi_0 \frac{\langle \phi_{0x}^2 \rangle}{\langle \phi_0^2 \rangle} \frac{\partial Y}{\partial \phi_0} + \langle \phi_{0x}^2 \rangle \frac{\partial^2 Y}{\partial \phi_0^2} \end{aligned}$$




FIG. 4.1. Normalized CDRs $\chi(Z,t)/F(t)$ for the initially unsymmetric double-delta distribution with $A = 0.6$. Line (DNS) and plus (model): initial CDRs; Dash (DNS) and diamond (model): final CDRs.

An exact solution can be obtained from (4.2) with the evaluated conditional averages (4.3) and the initial condition (2.5) which requires $\phi_1(0) = 0$

$$(4.4) \quad Y = \frac{1}{2} \left[1 + \operatorname{erf} \left(\frac{\phi_0 - \gamma e^r}{\sqrt{2}\Sigma} \right) + \left(1 - \exp[\phi_1 - \langle \phi_1 \rangle + \int_0^t \langle \frac{d\phi_1}{dt} | Z \rangle dt] \right) (2\langle Z \rangle - 1) \right].$$

We will calculate the CDR $\chi(Z,t) = \kappa \langle (\nabla Y)^2 | Z \rangle$, where ensemble average is taken over the level surface on which (ϕ_0, ϕ_1) satisfies $Y(\phi_0, \phi_1; t) = Z$. The expression obtained is then simplified by the first-order approximation of its Taylor expansion with respect to the mean $\langle \phi_1(t) \rangle$. This leads to

$$(4.5) \quad \chi(Z,t) = F(t) \exp \left[-2 \left(\operatorname{erf}^{-1}[(2Z-1)] - \left(1 - \frac{1}{\sqrt{1+f_{\phi_1}t}} \right) (2\langle Z \rangle - 1) \right)^2 \right],$$

where

$$(4.6) \quad \begin{aligned} F(t) &= \frac{f_{\phi_0}}{\sqrt{2\pi}\Sigma}, \\ f_{\phi_0} &= \kappa \frac{\langle (\phi_{x0})^2 \rangle}{\langle \phi_0^2 \rangle}, \\ f_{\phi_1} &= \frac{d\langle \phi_1^2 \rangle}{dt} / \langle \phi_1^2 \rangle. \end{aligned}$$

The time scales f_{ϕ_0} and f_{ϕ_1} are parameters of the present closure which must be input externally. Usually, they are reset at each time using a dynamical scheme, such as $f_{\phi_0} = \kappa \langle (\nabla Z)^2 \rangle / \langle Z^2 \rangle$ and $f_{\phi_1} = f_{\phi_0}$, so as to give correct evolution of the CDR. The CDR model (4.5) is compared with DNS of the diffusion equation with $\kappa = 1$. In the case of homogeneity, the use of the diffusion equation to validate the CDR model for turbulent mixing has a reasonable justification. Figure 4.1 shows the initial and final CDRs obtained by

the DNS and the CDR model (4.5) for the initially unsymmetric binary scalar with mean $\langle Z \rangle = 0.4$. For exhibiting the shift of the maximum, the CDRs are normalized by their amplitudes $F(t)$ and (4.5) is rescaled by the scalar's variances.

The CDR model (4.5) is no longer separable in Z and t . Its shape will shift while its amplitude decays with time. It is easy to verify $\chi(0.5, 0)/F(t) = 1$ and $\chi(\langle Z \rangle, \infty)/F(t) = 1$ so that the location of maximum dissipation shifts from initial interface $Z = 0.5$ to the scalar's mean $Z = \langle Z \rangle$. While $\langle Z \rangle = 0.5$, the equation (4.5) recovers the CDR model (2.8) from the amplitude mapping closure. Therefore, the CDR model (4.5) correctly describes asymptotic behaviors of CDR: the CDR's maximum asymptotically approaches $Z = \langle Z \rangle$, while initially being at $Z = 0.5$. We emphasize that (4.5) is the first term of the Taylor expansion of the CDR obtained from (4.4) with respect to the mean $\langle \phi_1(t) \rangle$. This simplified form gives the correct initial and asymptotic behavior of the unsymmetric binary mixing at the expense of an inaccurate description of the intermediate behavior. Indeed, it is well-known [9] that at short times, the CDR remains symmetric about the location of the initial interface. The symmetry point (location of maximum dissipation) begins to shift only after the elapse of a finite amount of time, depending on the extent of the initial asymmetry [14]. The present model predicts that the symmetry point begins to move immediately. A model which is also accurate at short times can be formulated from (4.4) in the general form

$$(4.7) \quad \chi(Z, t) = F(t) \exp \left[-2 \left(\operatorname{erf}^{-1}[(2Z - 1) - (1 - f(t))(2\langle Z \rangle - 1)] \right)^2 \right],$$

where $f(t)$ is a time-dependent function with $f(0) = 1$ and $f(+\infty) = 0$. The time-dependent function $f(t)$ is responsible for the shift of the CDR's shape. However, it is very difficult to write its expression explicitly, which needs a time scale as same as the case of amplitude function $F(t)$.

It has been shown that the mapping (4.1) is an appropriate approximation for a scalar gradient field. However, it is not expected that the mapping (4.1) makes the same accurate approximation to the scalar field as it does to the scalar gradient field itself. The reason is that a homogeneous random field is statistically orthogonal to its gradient field. The amplitude mapping (2.3) is an appropriate approximation to scalar fields but fails to approximate its gradient field. Generally speaking, the mapping closure carried out at the level of single-point PDFs is not valid for two-point PDFs such as gradient fields. This is the motivation to develop mapping closure approximation of higher orders. We expect that a higher-order approximation to a random field could produce a correct description of its gradient field.

5. Conclusion. We have developed a novel model of the conditional dissipation rate for turbulent mixing. The model is able to describe the asymptotic behavior of the CDR for either symmetric or unsymmetric initial double-delta distributions. The amplitude mapping closure has unsatisfactory asymptotic properties for the shift of the CDR's maximum. The problem can be solved using the extended mapping closure approximation developed in this paper. Further research is to account for the evolution of scalar variance by extending the CDR model (4.5). MCA can incorporate the effect of multiple time and length scales of practical interest in its predictions using more than one reference field. It provides a useful approach to describe statistics of turbulent mixing.

The author (G. W. He) is grateful for the very valuable discussions on the conditional dissipation rate with G. Kosaly and H. Pitsch. Special thanks are due to G. Kosaly for pointing out the exact solution (2.6). We thank S. S. Girimaji for his valuable comments on the shift process of the symmetric point.

REFERENCES

- [1] S. B. POPE, *PDF methods for turbulent reactive flows*, Progr. Energy. Combust. Sci., 11 (1985) pp. 119-192.
- [2] P. J. COLUCCI, F. A. JABERI, P. GIVI, AND S. B. POPE, *Filtered density function for large eddy simulation of turbulent reacting flows*, Phys. Fluids, 10 (1998), pp. 499-515.
- [3] W. K. BUSHE AND H. STEINER, *Conditional moment closure for large eddy simulation of nonpremixed turbulent reacting flows*, Phys. Fluids, 11 (1999) pp. 1896-1906.
- [4] H. PITSCH AND H. STEINER, *Large-eddy simulation of a turbulent piloted methane/air diffusion flame (Snadia flame D)*, Phys. Fluids, 12 (2000), pp. 2541-2554.
- [5] R. H. KRAICHNAN, *Closures for probability distribution*, Bull. Am. Phys. Soc., 34 (1989), p. 2298.
- [6] H. CHEN, S. CHEN, AND R. H. KRAICHNAN, *Probability distribution of a stochastically advected scalar field*, Phys. Rev. Lett., 63 (1989) pp. 2657-2660.
- [7] E. E. O'BRIEN AND T. L. JIANG, *The conditional dissipation rate of an initial binary scalar in homogeneous turbulence*, Phys. Fluids A, 3 (1991), pp. 3121-3123.
- [8] E. E. O'BRIEN AND A. SAHAY, *Asymptotic behavior of the amplitude mapping closure*, Phys. Fluids A, 4 (1992), pp. 1773-1775.
- [9] S. S. GIRIMAJI, *A mapping closure for turbulent scalar mixing using a time-evolving reference field*, Phys. Fluids A, 4 (1992), pp. 2875-2886.
- [10] V. ESWARAN AND S. B. POPE, *Direct numerical simulations of the turbulent mixing of a passive scalar*, Phys. Fluids, 31 (1988), pp. 506-520.
- [11] T. GOTOH AND R. H. KRAICHNAN, *Statistics of decaying Burgers turbulence*, Phys. Fluids, 5 (1993), pp. 445-457.
- [12] Y. KIMURA AND R. H. KRAICHNAN, *Statistics of an advected passive scalar*, Phys. Fluids, 5 (1993), pp. 2264-2277.
- [13] S. T. ORSZAG AND L. R. BISSONNETTE, *Dynamical properties of truncated Wiener-Hermite Expansions*, Phys. Fluids, 10 (1967), pp. 2603-2613.
- [14] T. L. JIANG, P. GIVI AND F. GAO, *Binary and trinary scalar mixing by Fickian diffusion - Some mapping closure results*, Phys. Fluids A, 4 (1992), pp. 1028-1035.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY(Leave blank)	2. REPORT DATE December 2000	3. REPORT TYPE AND DATES COVERED Contractor Report		
4. TITLE AND SUBTITLE Mapping closure approximation to conditional dissipation rate for turbulent scalar mixing			5. FUNDING NUMBERS C NAS1-97046 WU 505-90-52-01	
6. AUTHOR(S) Guowei He and R. Rubinstein				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) ICASE Mail Stop 132C NASA Langley Research Center Hampton, VA 23681-2199			8. PERFORMING ORGANIZATION REPORT NUMBER ICASE Report No. 2000-48	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Langley Research Center Hampton, VA 23681-2199			10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA/CR-2000-210631 ICASE Report No. 2000-48	
11. SUPPLEMENTARY NOTES Langley Technical Monitor: Dennis M. Bushnell Final Report To be submitted to Physics of Fluids.				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified-Unlimited Subject Category 34 Distribution: Nonstandard Availability: NASA-CASI (301) 621-0390			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) A novel mapping closure approximation (MCA) technique is developed to construct a model for the conditional dissipation rate (CDR) of a scalar in homogeneous turbulence. It is shown that the CDR model from amplitude mapping closure is incorrect in asymptotic behavior for unsymmetric binary mixing. The correct asymptotic behavior can be described by the CDR model formulated by the MCA technique. The MCA approach is outlined for constructing successive approximation to probability density function (PDF) and conditional moment.				
14. SUBJECT TERMS turbulent mixing, mapping closure, conditional dissipation rate, probability density function			15. NUMBER OF PAGES 12	
			16. PRICE CODE A03	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT	